



General Product

Specifications

Eureka Amber FS & Jindara Townsend FS

| Dimensions and Specifications | |
|---|---|
| Overall Dimension (Height) | 730 mm |
| Overall Dimension (Width) | 640 mm |
| Overall Dimension (Depth) | 502 mm |
| Firebox Dimension (Height) | 360 mm |
| Firebox Dimension (Width) | 538 mm |
| Firebox Dimension (Depth) | 292 mm |
| Door Opening Dimension (Height x Width) | 285 x 420 mm |
| Glass Viewing Size (Height x Width) | 270 x 410 mm |
| Flue Size | 150 mm |
| Back of Heater to Flue Centre | 176 mm |
| Shipping weight | 163 kg |
| Linings | Firebricks on walls and base |
| Baffle thickness | 8mm Lower Baffle, 6mm Upper Baffle |
| Glass Type | Flat, toughened 5mm ceramic |
| Hearth & Clearance requirements (Perforated outer flue kit) | |
| Min. Hearth Width | 820 mm |
| Min. Hearth Depth | 1060 mm |
| Min. Hearth Thickness | 24 mm |
| Min. In Front Of Unit | 550 mm |
| Rear Clearance | 250mm* |
| Side Clearance | 750 mm |
| Corner Clearance | 500mm, or 350mm** |
| | * denotes 900mm, 180 deg flue shield required |
| | ** denotes side wing kit to be fitted (purchased separately) |
| Hearth & Clearance requirements (Half Shield flue kit) | |
| Min. Hearth Width | 820 mm |
| Min. Hearth Depth | 1060 mm |
| Min. Hearth Thickness | 24 mm |
| Min. In Front Of Unit | 550 mm |
| Rear Clearance | 300 mm |
| Side Clearance | 825 mm |
| Corner Clearance | 475mm, or 300mm** |
| | **denotes side wing kit to be fitted (purchased separately) |
| CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION | |
| | |