Vindara

General Product

Specifications

Jindara Hamersley Mk2 FS

Dimensions and Specifications	
Overall Dimension (Height)	787 mm
Overall Dimension (Width)	770 mm
Overall Dimension (Depth)	570 mm
Firebox Dimension (Height)	339 mm
Firebox Dimension (Width)	582 mm
Firebox Dimension (Depth)	370 mm
Door Opening Dimension (Height x Width)	239 x 602mm
Glass Viewing Size (Height x Width)	263 x 566mm
Flue Size	150mm
Back of Heater to Flue Centre	200 mm
Shipping weight	190kg
Linings	Cast Iron Liners on walls, Firebricks in base
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements (Perforated Outer Flue Kit)	
Min. Hearth Width	1000mm
Min. Hearth Depth	1100mm
Min. Hearth Thickness	24mm
Min. In Front Of Unit	530mm
Rear Clearance	100*mm
Side Clearance	450mm
Corner Clearance	50mm
	* denotes standard flue shield required (included in wood heater)
Hearth & Clearance requirements (Half Shield Flue Kit)	
Min. Hearth Width	1000 mm
Min. Hearth Depth	1090 mm
Min. Hearth Thickness	24 mm
Min. In Front Of Unit	520 mm
Rear Clearance	125 mm
Side Clearance	475 mm
Corner Clearance	225 mm



General Product

Specifications

Jindara Hamersley Mk2 FS

Emissions and Efficiency	
Emissions	1.2g/kg
Efficiency	69%*
Peak Output	16kw
	*Peak efficiency % quoted
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER	
TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	