



# General Product Specifications

Eureka Jade FS MK2 & Jindara Franklin FS MK2

Dimensions and Specifications	
Overall Dimension (Height)	770 mm
Overall Dimension (Width)	585 mm
Overall Dimension (Depth)	455 mm
Firebox Dimension (Height)	330 mm
Firebox Dimension (Width)	483 mm
Firebox Dimension (Depth)	260 mm
Door Opening Dimension (Height x Width)	248 x 380 mm
Glass Viewing Size (Height x Width)	246 x 366 mm
Flue Size	150 mm
Back of Heater to Flue Centre	183 mm
Shipping weight	125 kg
Linings	Firebricks on walls
Baffle thickness	6mm Upper Baffle , 6mm lower baffle (double skinned)
Glass Type	Flat, toughened 5mm ceramic
Emissions and Efficiency	
Emissions	0.7g/kg
Efficiency	64%*
Peak Output	10kw
	*Peak efficiency % quoted
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	



# General Product Specifications

Eureka Jade FS MK2 & Jindara Franklin FS MK2

Hearth & Clearance requirements	
(Perforated outer flue kit, with additional 900mm, 180 deg stainless steel flue shield (purchased separately))	
Min. Hearth Width	780 mm
Min. Hearth Depth	885mm
Min. Hearth Thickness	6 mm
Min. In Front of Unit	300 mm
Rear Clearance	175 mm
Side Clearance	575 mm
Corner Clearance	375 mm
Hearth & Clearance requirements	
(Half Shield flue kit)	
Min. Hearth Width	780 mm
Min. Hearth Depth	860 mm
Min. Hearth Thickness	6 mm
Min. In Front of Unit	300 mm
Rear Clearance	150 mm
Side Clearance	600 mm
Corner Clearance	375 mm
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	