



General Product Specifications

Jindara Kimberley Mk3 Inbuilt

| Dimensions and Specifications | |
|--|---|
| Overall Dimension (Height) | 740 mm |
| Overall Dimension (Width) | 950 mm |
| Fascia Depth | 65 mm |
| Rear Casing Dimension (Height) | 600 mm |
| Rear Casing Dimension (Width) | 605 mm |
| Rear Casing Dimension (Depth) | 440 mm |
| Firebox Dimension (Height) | 309 mm |
| Firebox Dimension (Width) | 520 mm |
| Firebox Dimension (Depth) | 318 mm |
| Door Opening Dimension (Height x Width) | 213 x 540mm |
| Glass Viewing Size (Height x Width) | 228 x 504mm |
| Flue Size | 150mm |
| Back of Fascia to Flue Centre | 290 mm |
| Shipping weight | 138kg |
| Linings | Cast Iron Liners on walls, Firebricks in base |
| Baffle thickness | 8mm |
| Glass Type | Flat, toughened 5mm ceramic |
| Hearth & Clearance Requirements | |
| Min. Hearth Width | 940 mm |
| Min. Hearth Depth (in front of unit) | 550 mm |
| Min. Hearth Thickness | 18 mm |
| Clearance to Mantle Upright | 25 mm |
| Clearance to Mantel Shelf (from appliance base) | 1170 mm |
| Clearance to Mantel Breast Plate (from appliance base) | 1080 mm |
| Emissions and Efficiency | |
| Emissions | 0.3g/kg |
| Efficiency | 65%* |
| Peak Output | 12kw |
| | *Peak efficiency % quoted |
| CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION | |