



General Product

Specifications

Eureka Pearl Inbuilt & Jindara Tilga Inbuilt

	Masonry Insert	Zero Clearance Inser	
Overall Dimension (Height)	640 mm	674 mm	
Overall Dimension (Width)	855 mm	850 mm	
Fascia Depth	16 mm	3 mm	
Rear Casing Dimension (Height)	595 mm	N/A - See Zero Clear-	
Rear Casing Dimension (Width)	751 mm	N/A - See Zero Clear-	
Rear Casing Dimension (Depth)	484 mm	N/A - See Zero Clear-	
Firebox Dimension (Height)	362 mm		
Firebox Dimension (Width)	522 mm		
Firebox Dimension (Depth)	432 mm		
Door Opening Dimension (Height x Width)	256 x 522mm		
Glass Viewing Size (Height x Width)	285 x 570mm		
Flue Size	150mm		
Back of Fascia to Flue Centre	326 mm	N/A - See Zero Clear- ance Install Guide	
Shipping weight	162kg	256kg	
Linings	Cast Iron Liners on walls		
Baffle thickness	8mm		
Glass Type	Flat, toughen	Flat, toughened 5mm ceramic	
Hearth & Clearar	ce Requirements		
Min. Hearth Width	945 mm		
Min. Hearth Depth (in front of unit)	550 mm		
Min. Hearth Thickness	18 mm		
Clearance to Mantle Upright	55 mm		
Clearance to Mantel Shelf (from appliance base)	1500mm*		
Clearance to Mantel Breast Plate (from appliance base)	1410 mm		
	* denotes mantle deflector required (included in wood heater)		
Emissions a	nd Efficiency		
Emissions	1.0g/kg		
Efficiency	74%*		
Peak Output	12kw		
	*Peak efficiency % quoted		