



General Product

Specifications

Eureka Ruby Mk2 Inbuilt &

Jindara Grange Mk2 Inbuilt

	Masonry Insert	Zero Clearance Insert
Overall Dimension (Height)	705 mm	736 mm
Overall Dimension (Width)	935 mm	930 mm
Fascia Depth	16 mm	3 mm
Rear Casing Dimension (Height)	651 mm	N/A - See Zero Clearance
		Install Guide
Rear Casing Dimension (Width)	808 mm	N/A - See Zero Clearance Install Guide
Rear Casing Dimension (Depth)	484 mm	N/A - See Zero Clearance Install Guide
Firebox Dimension (Height)	408 mm	
Firebox Dimension (Width)	580 mm	
Firebox Dimension (Depth)	431 mm	
Door Opening Dimension (Height x Width)	275 x 580mm	
Glass Viewing Size (Height x Width)	310 x 630mm	
Flue Size	150mm	
Back of Fascia to Flue Centre	326 mm	N/A - See Zero Clearance Install Guide
Shipping weight	179kg	285kg
Linings	Cast Iron Liners on walls	
Baffle thickness	8mm	
Glass Type	Flat, toughened 5mm ceramic	
Hearth & Cleara	ince Requirements	
Min. Hearth Width	1000 mm	
Min. Hearth Depth (in front of unit)	520 mm	
Min. Hearth Thickness	18 mm	
Clearance to Mantle Upright	35 mm	
Clearance to Mantel Shelf (from appliance base)	1500mm*	
Clearance to Mantel Breast Plate (from appliance base)	1410 mm	
		ector required (included in d heater)
Emissions	and Efficiency	
Emissions	1.4g/kg	
Efficiency	68%*	
Peak Output	15kw	
	*Peak efficiency % quoted	