

Austroflamm - Woody Freestanding Wood Burning Fireplace

Made in Krenglbach, Austria

Dimensions

538 mm x 399 mm x 1027 mm

Viewing Dimensions

264 mm x 530 mm

7.0kW avg. Heat Output

- Energy efficiency: 64%
- Emissions: 1.0 grams/kg
- Flue Size: 150 mm
- Estimated max heat output: up to 120 sq meters
- 6-year Limited Warranty



TECHNICAL DATA

Clearances based on the installation of a 6" Triple skin flue kit, with an 8" Solid Decorative Flue Shield

Flue Configuration	Rear	Side	Front
Parallel no shielding	600	450	650
Parallel with 25mm Skamol	250	450	650

25mm Skamol Enclosure Board minimum of 1200mm wide and 1800mm high attached directly to wall.

Hearth depth includes 650mm in front of the appliance.

Thickness equal to 18mm Bellis Board or an equivalent product to be used under, in front and behind the fireplace.

Flue Configuration	Width	Depth	Thickness
Parallel no shielding	700	1649	18
Parallel with 25mm Skamol	700	1299	18

25mm Skamol Enclosure Board minimum of 1200mm wide and 1800mm high attached directly to wall.

Weight	Maximum Log Length	Flue Spigot	Flue Location
135 kilos	200mm	150mm	Top/Rear

Measurements

Overall

538/399/1027



Measurements shown are in millimeters unless otherwise stated and are in order of width/depth and height

Internal Fire Box

328/209/412

Viewing Area

264/N/A/530



Accessories



Open Base
538/399/300



Woody Log Holder
335/270/620

SPECIALITY FEATURES

Keramott Lining

Designed exclusively for Austroflamm the patented Keramott Lining excels by creating an exceptional ratio between thermal insulation and heat conduction. As a consequence the combustion chamber reaches higher temperatures whilst the cream finish enhances your view of the rolling flames.

Meeting DIBt requirements

The German Institute for Building Technology (DIBt for short) issues building inspectorate approvals for air-independent fireplaces. The Woody has been tested for tightness using a mechanical and thermal stress and has a door that automatically closes tightly making it suitable for tightly sealed homes when installed with outside ventilation.

Air Flow Technology

By controlling the airflow within the firebox, the glass is kept clear from soot, thus ensuring an uninterrupted view of the flames. The clean burn system introduces pre-heated combustion air to increase the heat output, and air flow technology also ensures that any solid particles and volatile gases produced by the fire are re-ignited and burnt off before they can re-enter the atmosphere.

High Performance and Heat Retention

Austroflamm continues to embody innovative design and technology that is ahead of its time. The Woody's beveled lid is crafted using robust cast iron whilst the black steel body of the unit delivers exceptional heat transfer creating a highly efficient fire.

Natural Wood Finishes

Cool to the touch the Woody is beautifully finished with a beech and natural walnut base and handle.

Tested for Australian Conditions

At the beginning of the 80s, Austroflamm recognized the need to free wood-burning fireplaces from their somewhat outdated image. Their aim was to develop fires that would revolutionize design and efficiency.

The Austroflamm Woody has been tested to adhere to the strict Australia Standards (AS2918 / AS4012/4013).