

The **SELECT WHITE** range offers true affordable value, ideal for applications that require a lower cost solution but with all the benefits of Far Infrared heating.

The **SELECT WHITE** Far Infrared heater has a white frame.

The heater is available in 3 different sizes, can be wall or ceiling mounted (making it ideal for passageways and office ceilings).

The **SELECT WHITE** is lightweight and the HS350-W and HS700-W are also ideal for use in office ceiling grids.

The Select panels are specifically designed to be maintenance free and to last for many years. For this reason, and to enable accurate temperature control and efficiency, the panels do not have any in-built controls and must be used in conjunction with Herschel iQ controls or equivalent. This will also ensure full compliance with European energy saving regulation (ERP Lot 20).



TECHNICAL DETAILS

SURFACE:	Aluminium
COLOUR:	White
HEATING ELEMENT:	Herschel COSIX© Cell Technology
REAR PANEL:	Steel with Herschel EASY-FIX System
FRAME:	White powder coated aluminium frame
SURFACE TEMPERATURE:	App. 85°C - 95°C
VOLTAGE:	220-240 V, 50/60Hz
PROTECTION CLASS:	IP44
CABLE:	2.5m power cable
INSTALLATION:	Wall or ceiling mounted *For ceiling mounting, use suitable fixings or connect to ceiling joist to secure heaters safely

CERTIFICATES:

WARRANTY



5 years (Refer to the warranty policy on Herschel-infrared.com for more detail including exclusions)

AVAILABLE MODELS

Model 311HM	Part No.	Dimensions	Weight	Rated Power	Heated Area
	HS350-W	59.5 x 59.5 x 2.5cm	5.2kg	350W	6-8m ²
	HS540-W	60 x 90 x 2.5cm	7.2kg	540W	9-12m ²
SELECT	HS700-W	59.5 x 119.5 x 2.5cm	9.2kg	700W	13-15m ²

The heated areas are an indicative guide only. The actual heated area will depend on the heat loss of the room which is influenced by many factors including construction type, external walls, window area and insulation levels. Always use the Herschel online calculator or contact your dealer or installer for an accurate specification.

The Select panel comes with one EASY-FIX mounting bracket. When installed, the front of the panel will extend a total of 5cm from the wall. The panel will radiate heat into the room and will perform best when mounted in a position free of any direct obstructions such as a sofa. The panel will need to be wired into the mains and this should be carried out by a suitably qualified electrician. Refer to installation instructions for full details.



6 REASONS WHY

- 🖌 100% natural
- Heats objects, not the air
- Less damp and mould
- ✓ Reduced energy use
- ✓ Maintenance free
- ✓ CO2 free when used with renewable energy

